

Planar EP6514K

4K LCD Display

The Planar® EP SeriesEP6514K display offers best-in-class 24x7 reliability with the stunning image quality of 4K resolution. The Ultra HD 65" display has multi-source viewing capability, supports 4K @ 60Hz and can be oriented in landscape or portrait. It comes fully loaded with advanced features that matter most to digital signage and other commercial applications such as an expansion slot supporting Intel's Open Pluggable Specification (OPS) and built-in speakers. The Planar EP Series EP6514K delivers superior performance and reliability for demanding public venue, corporate, and control room operations.



| SPECIFICATION | DETAIL |
|--------------------------------|--|
| Display Resolution | Ultra HD (3840 x 2160) |
| HD format | 4K UHD 2160p |
| 4K Modes | 1 x 3840x2160 @ 24/25/30/50/60Hz |
| Aspect Ratio | 16:9 |
| Display Technology | Edge-lit LED LCD |
| Screen Size | 65in. diagonal |
| Cabinet Dimensions (W x H x D) | 57.2" x 32.7" x 3.1" (1453.7mm x 829.7mm x 79.5mm) |
| Bezel Width | 0.5" (12mm) |
| Brightness (Typical) | 450 cd/m² |
| Response Time | 5.5ms |
| Frame Rate | 120Hz |
| Contrast Ratio | 4000:1 |
| Full viewing angle | 178° |
| Color Gamut | 72% NTSC |
| Display Color | 10 bit (1.07B colors) |
| Pixel Pitch | 0.372mm x 0.372mm |
| Weight | 110 lbs (50 kg) |
| Weight (Shipping) | 132 lbs (60 kg) |
| Backlight | Edge-Lit LED |
| Line Voltage | 100-240V; 50/60Hz |

| Power Consumption (max) | 280W |
|---------------------------------|--|
| Operating Environments | Temperature: 0-40° C (32-104° F); Humidity: 20-90% humidity non-condensing |
| Safety regulations | FCC Class A, cTUVus, CE |
| Standard Inputs | HDMI 1.4 x 4; Displayport 1.2, VGA, IR, OPS, OPS USB 2.0 x 2, OPS USB 3.0 |
| Audio Input | PC Audio in (Jack) |
| Audio Output | R/L Line out (Jack) |
| Multi-Source Views | PiP, Dual, Triple, Quad |
| Display Control | LAN RJ45, RS232 in, IR, Keypad (lockable) |
| Speakers | 10W x 2 built-in |
| Optional Accessories | Fixed wall mount, tilting wall mount, table stand |
| Auto Brightness Control | Ambient light sensor |
| Enclosure | Metal, Industrial |
| Orientation | Landscape/Portrait |
| Mounting | 400mm x 400mm VESA |
| Fanless | Yes |
| Recommended Usage | Up to 24x7 operation |
| Backlight life (1/2 brightness) | 50,000 hours |
| Bezel color | Black |
| Features | OPS slot, On/Off scheduling, TAA compliant |
| Warranty | 3 years Advance Exchange |
| Planar Part Number | 997-7928-00 |
| UPC | 8 10689 00237 6 |