

## Planar Standard 4K Models



	Planar® UltraRes™ Series	Planar® QE Series	Planar® EP Series	Planar® EPX Series	Planar® Simplicity™ Series 4K
<b>Sizes</b>	75", 86", 98"	75", 86", 98"	50", 58", 65"	100"	43", 50", 55", 65", 75", 86"
<b>Brightness</b>	500 nits	500 nits (75", 86" only) 400 nits (98" only)	500 nits	700 nits	500 nits (43", 50", 55", 65" only) 410 nits (75", 86" only)
<b>BackLight type: Edge-lit LED LCD</b>	75", 86" only	75", 86" only	50", 58" only	--	✓
<b>BackLight type: Direct-lit LED LCD</b>	98" only	98" only	65" only	✓	--
<b>Orientation</b>	Landscape, Portrait	Landscape, Portrait	Landscape, Portrait	Landscape, Portrait	✓ Landscape only
<b>ERO protection *</b>	Gorilla Glass	--	--	--	--
<b>Profile depth</b>	<4", ADA-compliant	--	--	--	--
<b>Outputs: DisplayPort 1.2</b>	✓	--	--	--	--
<b>Inputs: OPS</b>	✓	--	✓	✓	✓ 65", 75", 86" only
<b>Inputs: DisplayPort 1.2</b>	✓	✓	✓	✓	✓ 65", 75", 86" only
<b>Inputs: HDMI 1.4 (4K @ 30Hz)</b>	✓	✓	✓	✓	--
<b>Inputs: HDMI 2.0 (4K @ 60Hz)</b>	✓	✓	✓	✓	✓
<b>Inputs: HDCP 2.2</b>	✓	✓	✓	✓	✓
<b>Inputs: LAN RJ45, RS232</b>	✓	✓	✓	✓	✓
<b>Inputs: USB</b>	via OPS	Embedded Player	via OPS	via OPS	via OPS, 65", 75", 86" only
<b>Image adjustments by source</b>	✓	✓	Limited	Limited	--
<b>Scheduling</b>	✓	✓	✓	✓	✓
<b>Presets</b>	✓	--	Limited	Limited	--
<b>Media playback</b>	via OPS	Embedded Player	via OPS	via OPS	USB Embedded
<b>Browser</b>	via OPS	✓	via OPS	via OPS	✓
<b>SNMP <sup>2</sup></b>	✓	✓	✓	✓	--
<b>Remote monitoring <sup>3</sup></b> <i>(email notifications)</i>	✓	✓	✓	✓	--
<b>Web app</b>	✓	--	--	--	--
<b>Video wall tiling</b>	✓	--	--	--	--
<b>Serviceability <sup>1</sup></b> <i>(kickstand, removable tray)</i>	✓	--	--	--	--
<b>Audio speakers</b>	✓	✓	✓	✓	✓
<b>24x7 operation</b>	✓	✓	✓	✓	--
<b>Metal enclosure</b>	✓	✓	✓	✓	✓ 75", 86" only
<b>Redundant power <sup>4</sup></b>	✓	--	--	--	--
<b>Warranty included</b>	3-year	3-year	3-year	3-year	2-year
<b>Ideal applications</b>	Public spaces Digital branding & signage Collaboration Corporate Control Rooms	Digital branding & signage Collaboration Education Retail Public spaces	Digital branding & signage Corporate spaces Control rooms Retail Public spaces	Digital branding & signage Corporate spaces Control rooms Retail Public spaces	Retail Medical offices Reception areas Restaurants Hospitality

\*ERO protection — proprietary, protective bonded glass process that improves contrast and overall durability for high-traffic environments

<sup>1</sup>Field Serviceability — ability to swap most primary electronic components in the field

<sup>2</sup>SNMP — (Simple Network Managing Protocol) allows monitoring and control of the display over a network

<sup>3</sup>Remote monitoring — subset of SNMP; diagnostics for individual display components and display settings

<sup>4</sup>Redundant power — reduces downtime in the event of a power supply failure

# Planar Interactive Touch 4K Models



	Planar® UltraRes™ Series Touch	Planar® QE Series Touch	Planar® EP Series Touch	Planar® EPX Series Touch
<b>Sizes</b>	75", 86", 98"	75", 86", 98"	50", 58", 65"	100"
<b>Touch technology</b>	Infrared (IR)	Infrared (IR)	Infrared (IR), HID-compliant	Infrared (IR), HID-compliant
<b>Touch points, simultaneous</b>	32 points	20 points	20 points	20 points
<b>Fine Tip Stylus Support</b>	--	--	--	3mm stylus (included)
<b>Brightness</b>	500 nits	500 nits (75", 86" only) 400 nits (98" only)	500 nits	700 nits
<b>BackLight type: Edge-lit LED LCD</b>	✓ 75", 86" only	✓ 75", 86" only	✓ 50", 58" only	--
<b>BackLight type: Direct-lit LED LCD</b>	✓ 98" only	✓ 98" only	✓ 65" only	✓
<b>Orientation</b>	✓ Landscape, Portrait	✓ Landscape, Portrait (75", 86" only)	✓ Landscape, Portrait	✓ Landscape, Portrait
<b>ERO protection *</b>	✓ Gorilla Glass	✓ Gorilla Glass	✓	✓ 4mm glass with AG coating
<b>Profile depth</b>	✓ 4.1"	--	--	--
<b>Outputs: DisplayPort 1.2</b>	✓	--	--	--
<b>Inputs: OPS</b>	✓	--	✓	✓
<b>Inputs: DisplayPort 1.2</b>	✓	✓	✓	✓
<b>Inputs: HDMI 1.4 (4K @ 30Hz)</b>	✓	✓	✓	✓
<b>Inputs: HDMI 2.0 (4K @ 60Hz)</b>	✓	✓	✓	✓
<b>Inputs: HDCP 2.2</b>	✓	✓	✓	✓
<b>Inputs: LAN RJ45, RS232</b>	✓	✓	✓	✓
<b>Inputs: USB</b>	✓ via OPS	✓ Embedded Player	✓ via OPS	✓ via OPS
<b>Image adjustments by source</b>	✓	✓	✓ Limited	✓ Limited
<b>Scheduling</b>	✓	✓	✓	✓
<b>Presets</b>	✓	--	✓ Limited	✓ Limited
<b>Media playback</b>	✓ via OPS	✓ Embedded Player	✓ via OPS	✓ via OPS
<b>Browser</b>	✓ via OPS	✓	✓ via OPS	✓ via OPS
<b>SNMP <sup>2</sup></b>	✓	✓	✓	✓
<b>Remote monitoring <sup>3</sup> (email notifications)</b>	✓	✓	✓	✓
<b>Web app</b>	✓	--	--	--
<b>Video wall tiling</b>	✓	--	--	--
<b>Serviceability <sup>1</sup> (kickstand, removable tray)</b>	✓	--	--	--
<b>Audio speakers</b>	✓	✓	✓	✓
<b>24x7 operation</b>	✓	✓	✓	✓
<b>Metal enclosure</b>	✓	✓	✓	✓
<b>Redundant power <sup>4</sup></b>	✓	--	--	--
<b>Warranty included</b>	✓ 3-year	✓ 3-year	✓ 3-year	✓ 3-year
<b>Ideal applications</b>	Public spaces Digital branding & signage Collaboration Corporate Control Rooms	Digital branding & signage Collaboration Education Retail Public spaces	Digital branding & signage Corporate spaces Control rooms Retail Public spaces	Digital branding & signage Corporate spaces Control rooms Retail Public spaces

\*ERO protection — proprietary, protective bonded glass process that improves contrast and overall durability for high-traffic environments

<sup>1</sup>Field Serviceability — ability to swap most primary electronic components in the field

<sup>2</sup>SNMP — (Simple Network Managing Protocol) allows monitoring and control of the display over a network

<sup>3</sup>Remote monitoring — subset of SNMP; diagnostics for individual display components and display settings

<sup>4</sup>Redundant power — reduces downtime in the event of a power supply failure

[www.leyard.com](http://www.leyard.com) | [www.planar.com](http://www.planar.com)

**North America**  
1-866-475-2627  
sales@leyardgroup.com

**EMEA**  
+421-907-775-941  
sales.emea@leyardgroup.com

**APAC**  
+852 2326 0228  
info.asia@leyardgroup.com

**Japan**  
+81-3-6915-2768  
info.japan@leyardgroup.com

**Latin America**  
+55-41-3059-5100  
info.brazil@leyardgroup.com

Leyard and Planar are trademarks of Leyard Optoelectronics Co., Ltd. and Planar Systems, Inc. All other trademarks and service marks are the property of their holders. Copyright © 2019 Leyard Optoelectronics Co., Ltd. and Planar Systems, Inc. All rights reserved. This document may not be copied in any form without permission from Leyard or Planar. Information in this document is subject to change without notice. 1/19