



AMD FirePro™ SDI-Link

THE INDUSTRY'S CHOICE FOR GPU-ACCELERATED PROFESSIONAL VIDEO PIPELINES

Key Features:

- > Fully supports the new AMD FirePro™ V7900 SDI professional graphics card
- > Enables ultra-low-latency, high-throughput system performance via AMD DirectGMA (Graphics Memory Addressing) technology
- > Robust support for 3G SDI and other advanced signaling standards via third-party SDI I/O hardware compatibility and certification¹
- > Extensive support for advanced APIs such as OpenCL™ 1.1, OpenGL 4.2 and DirectX® 11
- > Highly scalable for advanced, synchronized multi-stream applications
- > Superior price/performance and value for OEMs, integrators and end-users

Introducing AMD FirePro™ SDI-Link – the next platform for GPU acceleration powering live/ on-air broadcast graphics and real-time video production/post-production pipelines.

AMD FirePro™ SDI-Link offers the required functionality and compatibility for today's integrated solutions powering 3D virtual sets, live sports and news graphics, video encoding and transcoding, on-set 3D VFX previz and professional video pipelines making use of the serial digital interface (SDI) video signal standard.

Built around an open-computing philosophy and close technology partnerships with leading SDI I/O PCIe card vendors, AMD FirePro™ SDI-Link equips OEMs and system integrators with powerful new options for flexibility and functionality when designing cost-effective, integrated technology solutions for their customers in broadcast, digital media production and post-production.

Leading video technology vendors are working closely with AMD to ensure compatibility with the AMD FirePro™ SDI-Link ecosystem for a broad range of applications requiring lowlatency GPU acceleration and comprehensive SDI video I/O functionality.

AMD FirePro™ SDI-Link includes broad and comprehensive support for the latest SDI signal formats including 3G SDI, as well as HDMI, AES-EBU digital audio, advanced SDI metadata, integrated RS-422 and GPIO transport control, and flexible support for 3D-stereographic 2K and 4K configurations.2

AMD FirePro™ SDI-Link is the evolution of GPU technology for broadcast graphics and real-time video pipelines.




"We are very excited to team up with AMD to offer developers even more options for their high-end broadcast and post production solutions. The combination of AMD's new FirePro[™] SDI-Link platform with DVS's Atomix family of video boards ensures an easy and low latency integration of DVS's reliable SDI input and output capabilities with the GPU power of AMD's FirePro™ SDI graphics cards."

> - Jürgen Heger, Senior Product Manager at DVS





FEATURES	BENEFITS
Support for the AMD FirePro™ V7900 SDI professional graphics card with AMD DirectGMA technology	Low-latency, high throughput GPU acceleration for real-time professional video and broadcast graphics pipelines
Support for industry-standard APIs such as OpenCL™ 1.1, OpenGL 4.2 and DirectX® 11	Maximum portability, flexibility and performance for software design
Easy to implement AMD FirePro™ SDI-Link SDK (software development kit) and related AMD global technical support	Short development time for integrated solutions built on the AMD FirePro™ SDI-Link platform
Integrated support for advanced SDI signal functionality including: 3G, multistream/3Dstereo, Dual-link, AES-EBU audio (embedded and discrete), and RS-422 and GPIO control ¹	Maximum compatibility with existing advanced SDI-centric pipelines and environments



² Features of third-party SDI I/O board vary; please confirm specifications with manufacturer before purchase.







^{© 2011} Advanced Micro Devices, Inc. All rights reserved. AMD, the AMD Arrow logo, FirePro, and combinations thereof are trademarks of Advanced Micro Devices, Inc. OpenCL is a trademark of Apple Inc. used with permission by Khronos. DirectX is a registered trademark of Microsoft Corporation in the United States and/or other jurisdictions. PCle is a registered trademark of PCI-SIG. All other names used in this document are for informational purposes only and may be trademarks of their respective owners. PID# 50550E